

IN THE CLAIMS:

Amended Claims

1. (Amended) A method for enabling a user to configure a customizable product in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, the method comprising:

receiving a request from a user of the client system to purchase the customizable product, wherein the customizable product includes one or more customizable components, wherein the customizable product comprises two or more electronic devices;

providing customizable component options of the customizable components to a client system for display after receiving said request;

receiving customizable component selections for at least one of the one or more customizable components of the customizable product in response to user input, wherein the customizable component selections applied to the customizable product specify a customized product; and

providing an image of the customized product to the client system for display, wherein the image of the customized product visually depicts the customizable component selections of the user.

25. (Amended) A method for enabling a user to configure a customizable product in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, the method comprising:

receiving a request from the user to purchase the customizable product, wherein the customizable product includes one or more customizable components, wherein the customizable product comprises two or more electronic devices;

providing an image of the customizable product to the client system for display after receiving the request, wherein images of at least a subset of the one or more customizable components are visually depicted proximate to their respective locations on the image of the customizable product;

cont
a2
receiving customizable component selections for at least one of the one or more customizable components of the customizable product, wherein said receiving customizable component selections includes receiving user input selecting the images of one or more of the customizable components.

35. (Amended) A method for enabling a user to configure a customizable product in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, the method comprising:

the client system providing a request to the electronic commerce server to purchase a customizable product, wherein the customizable product includes one or more customizable components, wherein the customizable product comprises two or more electronic devices;

the client system displaying customizable component options of the one or more customizable components after providing the request;

a3
the client system providing customizable component selections for at least one of the one or more customizable components of the customizable product to the electronic commerce server, wherein the customizable component selections applied to the customizable product specify a customized product; and

the client system displaying an image of the customized product, wherein the image of the customized product visually depicts the customizable component selections of the user.

40. (Amended) A method for enabling a user to configure a customizable product in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, the method comprising:

a4
the client system providing a request to the electronic commerce server to purchase a customizable product, wherein the customizable product includes one or more customizable components, wherein the customizable product comprises two or more electronic devices;

the client system displaying an image of the customizable product after receiving the request, wherein images of at least a subset of the one or more customizable

components are visually depicted proximate to their respective locations on the image of the customizable product;

the client system providing selections for at least one of the one or more customizable components of the customizable product to the electronic commerce server, wherein said providing selections includes providing user input selecting the images of the customizable components.

42. (Amended) A server system for enabling a user to configure a customizable product in an e-commerce transaction, the system comprising:

a processor;

a memory operatively coupled to said processor;

an input for coupling to a network, wherein the input is operable to receive a request from a user of the client system to purchase a customizable product, wherein the customizable product includes one or more customizable components, wherein the customizable product comprises two or more electronic devices;

a computer program stored in said memory, and wherein said computer program is executable to provide one or more customizable component selections of the customizable components to a client system for display after receiving said request;

wherein the input is further operable to receive customizable component selections from a user for at least one of the one or more customizable components of the customizable product, wherein the customizable component selections applied to the customizable product specify a customized product; and

wherein the computer program is further executable to provide an image of the customized product to the client system for display, wherein the image of the customized product visually depicts the customizable component selections of the user.

43. (Amended) A server system for enabling a user to configure a customizable product in an e-commerce transaction, the system comprising:

a processor;

a memory operatively coupled to said processor;

an input for coupling to a network, wherein the input is operable to receive a request from the user to purchase a customizable product, wherein the customizable product includes one or more customizable components, wherein the customizable product comprises two or more electronic devices;

a computer program stored in said memory, and wherein said computer program is executable to provide an image of the customizable product to the client system for display after receiving the request, wherein images of at least a subset of the one or more customizable components are visually depicted proximate to their respective locations on the image of the customizable product;

wherein the input is further operable to receive:

user input selecting the images of the customizable components; and

selections for at least one of the one or more customizable components of the customizable product.

44. (Amended) A memory medium comprising program instructions for enabling a user to configure a customizable product in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, wherein the program instructions are executable to implement:

receiving a request from a user of the client system to purchase the customizable product, wherein the customizable product includes one or more customizable components, wherein the customizable product comprises two or more electronic devices;

providing customizable component options of the customizable components to a client system for display after receiving said request;

receiving customizable component selections for at least one of the one or more customizable components of the customizable product in response to user input, wherein the customizable component selections applied to the customizable product specify a customized product; and

providing an image of the customized product to the client system for display, wherein the image of the customized product visually depicts the customizable component selections of the user.

New Claims

45. (New) A method for enabling a user to configure a measurement system in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, the method comprising:

receiving a request from a user of the client system to configure the measurement system, wherein the measurement system includes one or more customizable components, wherein at least one of the customizable components is a measurement device;

providing customizable component options of the customizable components to a client system for display after receiving said request;

receiving customizable component selections for at least one of the one or more customizable components of the measurement system in response to user input, wherein the customizable component selections applied to the measurement system specify a configured measurement system; and

providing an image of the configured measurement system to the client system for display, wherein the image of the configured measurement system visually depicts the customizable component selections of the user.

46. (New) The method of claim 45, wherein said providing the image of the configured measurement system includes providing customizable component selection images corresponding to the customizable component selections of the user.

47. (New) The method of claim 46, wherein at least a subset of the customizable component selection images are visually depicted at their respective locations on the image of the measurement system.

48. (New) The method of claim 47, wherein at least a subset of the customizable component selection images are visually depicted proximate to their respective locations on the image of the measurement system.

49. (New) The method of claim 45, wherein said providing the image of the measurement system includes providing text corresponding to the customizable component selections of the user;

wherein the text is visually depicted proximate to respective locations of the customizable components comprised in the image of the measurement system.

50. (New) The method of claim 45, wherein the image of the measurement system appears substantially like the purchased product.

51. (New) The method of claim 45, wherein the image of the measurement system is viewable by the user and used by the user to evaluate and confirm the customizable component selections.

52. (New) The method of claim 51, further comprising:

receiving one or more new customizable component selections for at least one of the one or more customizable components of the measurement system after said providing the image of the measurement system to the client system, wherein the new customizable component selections applied to the measurement system specify a new measurement system;

providing an image of the new measurement system, wherein the image of the new measurement system visually depicts the new customizable component selections of the user.

53. (New) The method of claim 45, wherein said receiving selections includes:

receiving user input selecting a first customizable component;

providing a menu of possible options for the first customizable component to the client system for display after the user input selecting the first customizable component;

receiving user input selecting one of the possible options for the first customizable

component

54. (New) The method of claim 45, wherein said providing the one or more customizable component options of the measurement system includes providing an image of the measurement system to the client system for display, wherein images of at least a subset of the one or more customizable components are visually depicted proximate to their respective locations on the image of the measurement system;

wherein said receiving customizable component selections includes:

receiving user input selecting an image of a first customizable component which is visually depicted proximate to its respective location on the image of the measurement system, wherein said receiving user input selecting the image of the first customizable component operates to select the first customizable component for configuration; and

receiving user input selecting a first customizable component option for the first customizable component, wherein the user input selecting the first customizable component option comprises the customizable component selection for the first customizable component.

55. (New) The method of claim 54, wherein said receiving user input selecting the image of the first customizable component further includes:

receiving user input indicating a position of a cursor of the client system proximate to the location of the image of the first customizable component visually depicted on the image of the measurement system.

56. (New) The method of claim 54, wherein said receiving customizable component selections further includes:

providing a menu comprising the customizable component options of the first customizable component for display on the client system after said receiving user input selecting the image of the first customizable component.

57. (New) The method of claim 56, wherein the menu comprising the customizable component options includes text indicating the customizable component options.

58. (New) The method of claim 56, wherein the menu comprising the customizable component options includes images indicating the customizable component options.

59. (New) The method of claim 56, wherein the menu is operable to be displayed proximate to the location of the image of the first customizable component

60. (New) The method of claim 54, wherein said receiving customizable component selections further includes:

providing a sequence of images corresponding to the customizable component options of the first customizable component after said receiving user input selecting the image of the first customizable component.

61. (New) The method of claim 54, wherein said receiving user input selecting the first customizable component option includes:

providing customizable component option images corresponding to the customizable component options of the first customizable component;

receiving user input selecting a first customizable component option image corresponding to the first customizable component option.

63. (New) The method of claim 54, further comprising:

providing an image of the first customizable component option for display on the client system in response to said receiving user input selecting the first customizable component option for the first customizable component.

64. (New) The method of claim 54, further comprising:

the client system displaying the image of the measurement system in response to said providing the one or more customizable component options of the customizable components to the client system, wherein images of at least a subset of the one or more customizable components are visually depicted proximate to their respective locations on the image of the measurement system;

wherein, for each customizable component, the one or more customizable component options are displayed proximate to the image of the customizable component.

65. (New) The method of claim 45, further comprising:

the client system displaying one or more customizable component options of the customizable components in response to said providing the one or more customizable component options of the customizable components to the client system; and

the client system displaying the image of the measurement system in response to said providing the image of the measurement system to the client system for display, wherein the displayed image of the measurement system visually depicts the customizable component selections of the user.

66. (New) The method of claim 65, wherein the customizable component selections include one or more of: measurement card; cable, signal conditioning modules and transducer.

67. (New) A method for enabling a user to configure a computer system in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, the method comprising:

receiving a request from a user of the client system to purchase the computer system, wherein the computer system includes one or more customizable components;

providing customizable component options of the customizable components to a client system for display after receiving said request;

receiving customizable component selections for at least one of the one or more customizable components of the computer system in response to user input, wherein the

customizable component selections applied to the computer system specify a computer system; and

providing an image of the computer system to the client system for display, wherein the image of the computer system visually depicts the customizable component selections of the user.

68. (New) The method of claim 67, wherein said providing the image of the computer system includes providing customizable component selection images corresponding to the customizable component selections of the user.

69. (New) The method of claim 68, wherein at least a subset of the customizable component selection images are visually depicted at their respective locations on the image of the computer system.

70. (New) The method of claim 68, wherein at least a subset of the customizable component selection images are visually depicted proximate to their respective locations on the image of the computer system.

71. (New) The method of claim 67, wherein said providing the image of the computer system includes providing text corresponding to the customizable component selections of the user;

wherein the text is visually depicted proximate to respective locations of the customizable components comprised in the image of the computer system.

72. (New) The method of claim 67, wherein the image of the computer system appears substantially like the purchased product.

73. (New) The method of claim 67, wherein the image of the computer system is viewable by the user and used by the user to evaluate and confirm the customizable component selections.

74. (New) The method of claim 73, further comprising:

receiving one or more new customizable component selections for at least one of the one or more customizable components of the computer system after said providing the image of the computer system to the client system, wherein the new customizable component selections applied to the computer system specify a new computer system;

providing an image of the new computer system, wherein the image of the new computer system visually depicts the new customizable component selections of the user.

75. (New) The method of claim 67, wherein said receiving selections includes:

receiving user input selecting a first customizable component;

providing a menu of possible options for the first customizable component to the client system for display after the user input selecting the first customizable component;

receiving user input selecting one of the possible options for the first customizable component.

76. (New) The method of claim 67, wherein said providing the one or more customizable component options of the computer system includes providing an image of the computer system to the client system for display, wherein images of at least a subset of the one or more customizable components are visually depicted proximate to their respective locations on the image of the computer system;

wherein said receiving customizable component selections includes:

receiving user input selecting an image of a first customizable component which is visually depicted proximate to its respective location on the image of the computer system, wherein said receiving user input selecting the image of the first customizable component operates to select the first customizable component for configuration; and

receiving user input selecting a first customizable component option for the first customizable component, wherein the user input selecting the first customizable component option comprises the customizable component selection for the first customizable component.

78. (New) The method of claim 76, wherein said receiving user input selecting the image of the first customizable component further includes:

receiving user input indicating a position of a cursor of the client system proximate to the location of the image of the first customizable component visually depicted on the image of the computer system.

79. (New) The method of claim 76, wherein said receiving customizable component selections further includes:

providing a menu comprising the customizable component options of the first customizable component for display on the client system after said receiving user input selecting the image of the first customizable component.

80. (New) The method of claim 78, wherein the menu comprising the customizable component options includes text indicating the customizable component options.

81. (New) The method of claim 78, wherein the menu comprising the customizable component options includes images indicating the customizable component options.

82. (New) The method of claim 78, wherein the menu is operable to be displayed proximate to the location of the image of the first customizable component

83. (New) The method of claim 76, wherein said receiving customizable component selections further includes:

providing a sequence of images corresponding to the customizable component options of the first customizable component after said receiving user input selecting the image of the first customizable component.

84. (New) The method of claim 76, wherein said receiving user input selecting the first customizable component option includes:

providing customizable component option images corresponding to the customizable component options of the first customizable component;

receiving user input selecting a first customizable component option image corresponding to the first customizable component option.

85. (New) The method of claim 76, further comprising:

providing an image of the first customizable component option for display on the client system in response to said receiving user input selecting the first customizable component option for the first customizable component.

86. (New) The method of claim 76, further comprising:

the client system displaying the image of the computer system in response to said providing the one or more customizable component options of the customizable components to the client system, wherein images of at least a subset of the one or more customizable components are visually depicted proximate to their respective locations on the image of the computer system;

wherein, for each customizable component, the one or more customizable component options are displayed proximate to the image of the customizable component.

87. (New) The method of claim 67, further comprising:

the client system displaying one or more customizable component options of the customizable components in response to said providing the one or more customizable component options of the customizable components to the client system; and

the client system displaying the image of the computer system in response to said providing the image of the computer system to the client system for display, wherein the displayed image of the computer system visually depicts the customizable component selections of the user.

cont
Al 88. (New) The method of claim 87, wherein the customizable component selections include one or more of: display, peripheral devices, storage devices, memory size, communication type, memory type.
